DYE-A-LOG VENEERS

Natural Dyed Koto | K.Q.071

Product Information

Commercial Name:	Koto
Origin:	Africa
Density:	600 Kg/m³
Hardness:	Low
Texture:	Big
Porosity:	High
Natural Color:	White - Yellow
Thickness:	0.5 - 0.6 mm
Length:	1000 - 3200 mm, 39” - 126”
Width:	120 - 250 mm, 4.7” - 9.8”

FSC
www.fdc.org

Guidelines on fabrication, finishing and UV resistance.

Our veneers, both natural dyed and reconstituted, are applied with the same conventional woodworking techniques used for all wood veneers. We stand behind the fabrication recommendations of the Architectural Woodworking Institute (AWI) and its standards. Reconstituted Veneer may not match when spliced in panels or backed veneer sheets due to the nature of our manufacturing process and of reconstituted veneers in general. Please discuss with your fabricator in advance how these limitations may affect the final appearance of your project upon completion. Clear finishing is recommended since the color is predetermined. **WARNING:** Wood veneers, like other materials, will alter in color due to exposure to ultraviolet (UV) light or simply aging of the wood. Fading may be reduced by the use of non-yellowing finishes that contain UV inhibitors. Materials Inc. will suggest coatings to be used by your fabricators and will make control samples available in a select variety of sheen levels.

For more information,
please scan QR Code

18 Johnson Ave., Hackensack, NJ 07601
info@materials-inc.com | materials-inc.com